



STOCKMANS RIDGE
AUSTRALIAN SPECIES TIMBER



Stockmans Ridge

A NEW GENERATION OF ENGINEERED FLOORING THAT HONOURS THE BEAUTY AND ELEGANCE OF AUSTRALIAN HARDWOOD

Benefits of using AUSWOOD's Hardwood Flooring:

- State of the art manufacturing
- Australian hardwood species options
- Superior "Platinum Coating technology"
- Increased stability
- Environmental sustainability
- Low maintenance
- Excellent value

[FIND OUT MORE HERE](#)

Ph: 02 9792 8986

www.auswood.com.au

www.stockmansridge.com.au



Välinge

NOW AVAILABLE IN A RANGE OF CLASSIC AUSTRALIAN TIMBERS



Sydney Blue Gum



Spotted Gum



Jarrah



Blackbutt



Grey Ironbark



Brush Box

INCREASED STABILITY

With its specially designed construction, Stockmans Ridge Timber flooring will provide you with years of enjoyment. Guaranteed to be free of defects for 25 years.

WIDE BOARDS

Stockmans Ridge flooring comes in an extra-wide 186mm board presenting the full beauty and elegance of Australian hardwood.

TOUGHER SURFACE COATING

A new 'Platinum Coating Technology' takes scratch and dent resistance to a higher level.

CARE AND MAINTENANCE

Proper care and maintenance will help to keep your Stockmans Ridge floor looking as new as possible.

PROTECTION

Use normal timber floor protection such as floor rugs and doormats to avoid wear damage and scratches to your new flooring surface. Timber floors will darken with exposure to light. Move rugs and mats regularly to avoid patches of different colours.

CLEANING AND MAINTENANCE

Regular sweeping and cleaning with Bona products is highly recommended. A wide range of Bona flooring maintenance products can be purchased from your local Carpet Court Store.

RE-SANDING AND RE-COATING

Due to its specially designed structure and high stability, Stockmans Ridge flooring will retain a flat surface for its lifetime. Should re-coating be required, use a buffing pad to rough up existing coating on the whole Stockmans Ridge range. Fine grit sanding paper can be used on Stockmans Ridge flooring to remove existing coating. Always seek advice from your supplier about the most appropriate re-coating process.

SPECIFICATIONS

SPECIES	Sydney Blue Gum, Spotted Gum, Jarrah, Blackbutt, Grey Ironbark, Brush Box
VENEER	0.6mm face veneer nominal thickness
SUBSTRATE	Cross-laminated plantation Eucalyptus
SIZES	1830 x 186 x 14/0.6mm
CLICK	Patented Välinge click locking system
FINISH	14 acrylic coats; high dent and scratch resistance, micro-bevelled
WARRANTY	25 year domestic or 5 year commercial warranty
STANDARDS	Manufactured to meet globally recognised standards: ASTM D-2394; ASTM D-3359 and ASTM D-4060
PACKING	186mm wide – 6 pieces covering 2.042m ² per carton. 55 cartons or 112.325m ² per pallet
NESTING	14/0.6mm thickness: 2/6 of 600, 900 or 1200mm



AUSWOOD INTERNATIONAL PTY LTD

P 02 9792 8986

E enquiries@stockmansridgeflooring.com.au

www.stockmansridgeflooring.com.au

www.auswood.com.au

NB: Swatches are only indicative of colour and should be used as a guide only. Current as of April 2019. As timber is a natural material a vast degree of variety in colour, texture and naturally occurring feature can be found. Ranges may vary from store to store. Please contact your nearest store for more information.